



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	REVISE NOTE	JACK	4/9-09'

C	SHELL	1	copper alloy,t=0.40mm
B	CONTACT	5	copper alloy,t=0.25mm
A	HOUSING	1	High temperature with g.r,UL94V-0
NO	DESCRIPTION	QTY	MATERIAL
UNLESS OTHERWISE SPECIFIED TOLERANCES			
DECIMALS:		ANGLES:	
X	:±0.5	X	:±2°
X.X	:±0.3	X.X	:±1°
X.XX	:±0.2	X.XX	:±0.2
3G ENTERPRISE LIMITED			
TITLE		Mini usb 5s B Type Smt(Post=1.0H)	
DWN	JACK	PART NO. 2UB2006-5P0115	
CHKD	SCALE:	UNIT: mm	
APVD	SIZE:	A3 SHEET: 10F 1 REV:A	
CUSTOMER COPY			

Specification:

- 1 Current rating: 1 A Max.
- 2 Dielectric withstanding
- 3 voltage: 100 V(ac) for 1 min.
- 4 Contact resistance: 50 mΩ Max.
- 5 Insulation resistance: 100 MΩ Min.
- 6 Total mating force: 3.57 Kgf Max.
- 7 Total unmating force: 0.71 Kgf Min.
- 8 Temperature range: -25°C~85°C