



Dimensions List

PIN	DIM	DIM A	DIM B	PIN	DIM	DIM A	DIM B
2*01	2.00	0.00	2*21	42.00	40.00		
2*02	4.00	2.00	2*22	44.00	42.00		
2*03	6.00	4.00	2*23	46.00	44.00		
2*04	8.00	6.00	2*24	48.00	46.00		
2*05	10.00	8.00	2*25	50.00	48.00		
2*06	12.00	10.00	2*26	52.00	50.00		
2*07	14.00	12.00	2*27	54.00	52.00		
2*08	16.00	14.00	2*28	56.00	54.00		
2*09	18.00	16.00	2*29	58.00	56.00		
2*10	20.00	18.00	2*30	60.00	58.00		
2*11	22.00	20.00	2*31	62.00	60.00		
2*12	24.00	22.00	2*32	64.00	62.00		
2*13	26.00	24.00	2*33	66.00	64.00		
2*14	28.00	26.00	2*34	68.00	66.00		
2*15	30.00	28.00	2*35	70.00	68.00		
2*16	32.00	30.00	2*36	72.00	70.00		
2*17	34.00	32.00	2*37	74.00	72.00		
2*18	36.00	34.00	2*38	76.00	74.00		
2*19	38.00	36.00	2*39	78.00	76.00		
2*20	40.00	38.00	2*40	80.00	78.00		

技术要求:

- 1, 额定电流: 2A
- 2, 额定电压: 500V 绝缘电阻: 1000MΩ MIN.at DC500V
- 3, 适用温度: -40° C to +105° C.
- 4, 焊接温度: 280° C (3-5秒)
- 5, 塑件表面平整, 光洁, 无毛刺、气泡, 针表面无氧化、电镀不良等
- 6, 本产品符合ROHS环保要求
- 7, 未注公差为±0.20
- 8, PART NO. 2PH-3043-0 □□

2-40PIN

REV	ECN NO OR DESCRIPTION	REVISED	DATE

B	CONTACT	2-40	BRASS	GOLD FLASH
A	HOUSING	1	PAST UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
3G ENTERPRISE LIMITED				
TITLE		PH2.0 SMT6.5 PA4.0 PB2.5 PH10.5		
DECIMALS:	ANGLES:	PART NO. 2PH-3043-0 □□		
X : ±0.38	X : ±2°	DWN	JACK	SCALE: N/A
X : X : ±0.25		CHKD		UNIT: mm
X : X : ±0.15		APVD		SIZE: A3
X : X : ±0.05		SHEET: 1 OF 1		
REV: A				
CUSTOMER COPY(YB)				

