



规格说明 Specifications:

电气特性 Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触电阻: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能 Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料 Material:

1. 塑胶 Housing:
Hing Temperature Thermoplastics,
UL 94V-0 PBT White/Black
2. 端子 Contact: Copper Alloy C2680
3. 外壳 Shell: Copper Alloy C2680/SPCC

电镀 Finish:

1. 端子 Contact: Plated Gold in Mating Area;
Tin Dn Solder Talls
2. 外壳 Shell:
Nickel Plating

GENERAL TOLERANCE		DWG NO.	APPD:	WIND	Scale
X.±0.45	X.±5°	JYSA0804-001			1:1
X±0.35	X.±2°	Title	USB A/F 90° DIP (无盖弯脚卷边)		UNIT mm
.XX±0.25	.XX.±1°	Part NO.	JYS-USB137-022	Date	2012/04/13
.XXX±0.15	.xxx.±0.5°				
SHEET 1/1					