



P8	DATA1
P7	DATO
P6	VSS
P5	CLK
P4	VDD
P3	CMD
P2	CD/DAT3
P1	DAT2
PIN NUMBER	SIGNAL NAME

- NOTE:
- ELECTRICAL CHARACTERISTICS
 - CONTACT RESISTANCE: 50 milliohms MAX.
 - INSULATION RESISTANCE: 1,000 Megohms MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC MIN FOR 1 MINUTE.
 - MECHANICAL CHARACTERISTICS
 - RETENTION FORCE: MIN. 30~90gf/PIN
 - DURABILITY: 5,000 CYCLES
 - PRODUCT COMPLIED WITH ROHS

3	SHELL	1	STAINLESS STEEL	
2	CONTACT	8	COPPER ALLOY MATING AREA Au PLATED	
1	HOUSING	1	THERMOPLASTIC UL94V-0, BLACK	
ITEM	NAME	QTY/EACH	MATERIAL/FINISHED	REMARK

GENERAL TOLERANCE		DWG NO.	JYSA0528-012	APPD:	WIND	Scale	1:1
X.±0.45	X.±5'	Title	短型 T-FLASH 3.25H CONN	CHKD:		UNIT	mm
X±0.35	X.±2'	Part NO.	JYS-TF325-022	DR:			
.XX±0.25	.XX.±1'	Date	2013/10/31				
.XXX±0.15	.xxx.±0.5'						
SHEET	1/1						


 杰宇森电子有限公司
 JIE YU SEN ELECTRONIC CO., LTD.

REV.	ECN.NO.	MODIFY CONTENT	DATE
A		NEW	2013/10/31